RMZ-1214-E12

Temperature sensor, external air temperature + internal product simulator sensor

Туре	RMZ-1214-E12, 1 internal product simulator NTC + 1 external air probe NTC
Applications	Food storage, Production areas
Simulator	Internal volume of 30 ml PUR Resin (<0.21W/mK Thermal conductivity)
Measuring range:	-35°C to +50°C
Accuracy:	±0,5 °C (-20°C up to 40°C)
Resolution	0.1°C
Operating temperature	-35°C to +50°C
Storage temperature	-40°C to +55°C
Measuring rate	Standard 5 min, can be set 1 min to 6 h
Measuring mode	Online via RF wireless Zigbee
Memory	900 samples
Power	Battery operated 3.6V LiTCL AA type (included)
Battery life	> 3 years at measuring rate 5min @ 25°C > 5 years at measuring rate 10min @ 25°C
Protection class	IP 65
Housing	ABS, white
Dimensions	77x50x34 mm
Weight	132 g
Radio Frequency	ISM 2,4 - 2,5 GHz
Certifications	Conforms to standard EN12830 for HACCP Conforms to CE / FCC
Transmit Power	6.3 mW (+8 dBm)
Transmission distance	Up to 60 m Indoor range
A.I. 161 .1 .1 .1 .1 .1	

All specifications in this document are subject to change without prior notice



Highlights

External air temperature plus internal product simulator sensor
Cost effective device
Ideal for cold storage
Simple Do-It-Yourself installation
Logging to the cloud
Alarming via email and SMS
Excellent replacement for loggers



More information

BELGIUM

T +32 89 51 50 12 M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87 M info@rmoni.com



Raise your quality standards with Rmoni