

RMZ-1214-E51

Temperature sensor, 1 external digital temperature probe



Highlights

- Easy annual calibration
- Simple Do It Yourself installation
- Digital temperature probe via external cable
- M8 style push-pull connector, IP68
- ~Swap probe to calibrate~
- Logging to the cloud
- Compatible with RMZ series
- Alarming via email and SMS
- Excellent replacement for loggers



More information

BELGIUM

T +32 89 51 50 12
M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87
M info@rmoni.com

Type	RMZ-1214-E51, 1 external digital temperature probe External probe TDIGL000_DS1xx or TDIGL000_DS2xx (not included): Cable length to be specified at order : RMZ-1214-E51-DS0801 = 1m cable length M8 connector RMZ-1214-E51-DS0802 = 2m cable length M8 connector RMZ-1214-E51-DS0805 = 5m cable length M8 connector RMZ-1214-E51-DS1201 = 1m cable length M12 connector RMZ-1214-E51-DS1202 = 2m cable length M12 connector RMZ-1214-E51-DS1205 = 5m cable length M12 connector
Applications	Food storage, Production areas
Measuring range:	-50°C to +100°C
Accuracy:	±0,3°C (-20°C up to 40°C)
Resolution	0.1°C
Operating temperature	-35°C to +50°C
Storage temperature	-40°C to +55°C
Measuring rate	Standard 15 min, can be set 15 min to 6 h
Measuring mode	Online via RF wireless Zigbee
Memory	900 samples
Power	Battery operated 3.6V LiTCL AA type (included)
Battery life	> 2 years at measuring rate 15min @ 25°C
Protection class	IP 65
Housing	ABS, white
Dimensions	77x50x34 mm
Weight	92 g
Radio Frequency	ISM 2,4 - 2,5 GHz
Certifications	Conforms to standard EN12830 for HACCP Confirms to CE / FCC
Transmit Power	6.3 mW (+8 dBm)
Transmission distance	Up to 60 m indoor range



Raise your quality
standards with Rmoni