# RMZ-1215-R51

## Zigbee repeater, 3x 10V

Туре	RMZ-1215-R51
Applications	Food Healthcare & Pharma
Sensors	3 external linear inputs 010V (420 mA via 100-500 ? load resistor)
Measuring range	-40°C to +60°C
Accuracy	± 2% Full Scale Equivalent
Resolution	1 mV or rescaled parameter
Memory	12.000 samples
Operating temperature	-10°C to +40°C
Storage temperature	-40°C to +55°C
Measuring rate	Standard 5 min, can be set 1 min to 6 h
Measuring mode	Online via Zigbee wireless network
Power	9-24VDC power supply via external adapter (included)
Protection class	IP 40
Housing	Polycarbonate, UV stabilized
Dimensions	81 x 80 x 55 mm
Weight	500g (including adapter)
Certifications	Conforms to standard FDA21CFR11 Conforms to standard EN12830

All specifications in this document are subject to change without prior notice



#### Highlights

Attaches up to 3 linear inputs (0..10V)
Excellent price/performance ratio
Expands wireless network
Self configuring
Can be cascaded to cover wide areas
Redundant installations supported
Self healing in case of network failure
Stores over 12.000 readings



### More information

#### **BELGIUM**

T +32 89 51 50 12 M info@rmoni.com

# THE NETHERLANDS

T +31 74 265 77 87 M info@rmoni.com



Raise your quality standards with Rmoni