

RMX-1218-G65

LogTrackMeas digital, 4G + GPS



Type	RMX-1218-G65 GSM/GPS Tracker with four digital sensor inputs
Applications	Cold Chain Logistics
Sensors	4x External Digital DS18B, contact inputs
Accuracy	Cf TDIG sensor datasheet
Resolution	Cf TDIG sensor datasheet
Memory	18.725 samples
WAN Interface	2+4G GSM, with built-in GPS
SIM Card	Micro SIM, NOT included
Antenna	Internal GSM antenna, internal 2.4Ghz wire antenna, Internal GPS antenna
Localization	GPS High sensitivity for indoor reception, better than -158 dBm with A-GPS
Localization accuracy	Up to 0.8 meter
Operating temperature	-40°C to +80°C
Storage temperature	-40°C to +85°C
Power	12/24V DC power via cable (EU and International power plug versions available)
Protection class	IP 40
Housing	Flame Retardant ABS UL94-V0
Dimensions	92(111)X58X39mm
Weight	200 g (including adapter)

All specifications in this document are subject to change without prior notice

Highlights

Permanent automatic temperature / contact monitoring
Real time data transmission via GSM/4G (2G fallback)
Localization via GPS
Designed for transport applications
Up to four external direct connected digital temperature sensors; can be calibrated
Compact and robust for easy installation under dashboard
API interface available for third-party integration



More information

BELGIUM

T +32 89 51 50 12

M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87

M info@rmoni.com



Raise your quality standards with Rmoni