

RMX-1218-G68

LogTrackMeas analog, 4G + GPS



Type	RMX-1218-G68 GSM/GPS Tracker with four analog sensor inputs
Applications	Cold Chain Logistics
Sensors	4x wired external NTC, contact inputs.
Accuracy	± 0,5°C
Resolution	0.1°C
Memory	18.725 samples
WAN Interface	2+4G GSM, with built-in GPS
SIM Card	Micro SIM, NOT included
Antenna	Internal GSM antenna, internal 2.4Ghz wire antenna, Internal GPS antenna
Localization	GPS High sensitivity for indoor reception, better than -158 dBm with A-GPS
Localization accuracy	Up to 0.8 meter
Operating temperature	-40°C to +80°C
Storage temperature	-40°C to +85°C
Power	12/24V DC power via cable (EU and International power plug versions available)
Protection class	IP 40
Housing	Flame Retardant ABS UL94-V0
Dimensions	92(111)X58X39mm
Weight	200 g (including adapter)

All specifications in this document are subject to change without prior notice

Highlights

Permanent automatic temperature / contact monitoring
Real time data transmission via GSM/4G (2G fallback)
Localization via GPS
Designed for transport applications
Up to four external direct connected NTC temperature, door sensors; can be calibrated
Compact and robust for easy installation under dashboard
API interface available for third-party integration



More information

BELGIUM

T +32 89 51 50 12

M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87

M info@rmoni.com



Raise your quality
standards with Rmoni