

RMX-1225-E63

Wireless temperature logger (On/Off/Alarm)



Type	RMX-1225-E63
Applications	Cold Chain Logistics
Sensors	1 internal temperature sensor 1 external temperature sensor (option) 1 external 'monitor' contact (option)
Accuracy	±0,5 °C (-20°C to 40°C) with calibration
Resolution	0.1°C
Memory	18 725 samples
Operating temperature	-35°C to +60°C
Storage temperature	-40°C to +80°C
Measuring rate	Standard 5 min, can be set 1 min to 6 h
Measuring mode	Online via broadcast to LogPass; Online via unicast to LogBase; Offline logging – finds LogBase and uploads (unicast)
Alarming	Activation via on/off button on device ('On Duty') optional via external link, e.g. case cover Signaling via green/red LED during 'On Duty'.
Power	Battery 3,6 V lithiumTCL (RMONI 2450mAh)
Battery life	>12 months at measuring rate 15min @ 25°C
Protection class	IP 54
Housing	PMMA glossy white
Dimensions	80x70x28mm
Weight	135g

All specifications in this document are subject to change without prior notice

Highlights

- Cost effective device
- Start/stop monitoring feature
- Clear in-alarm LEDs
- Compact design
- Easy to clean
- Internal or external sensor probe
- External switch "in use"
- Logging to the cloud
- Alarm via email and SMS
- Excellent replacement for loggers



More information

BELGIUM

T +32 89 51 50 12
M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87
M info@rmoni.com



Raise your quality
standards with Rmoni