RMX-1225-E63

Wireless temperature logger (On/Off/Alarm)

Туре	RMX-1225-E63
Applications	Cold Chain Logistics
Sensors	1 internal temperature sensor 1 external temperature sensor (option) 1 external 'monitor' contact (option)
Accuracy	±0,5 °C (-20°C to 40°C) with calibration
Resolution	0.1°C
Memory	18 725 samples
Operating temperature	-35°C to +60°C
Storage temperature	-40°C to +80°C
Measuring rate	Standard 5 min, can be set 1 min to 6 h
Measuring mode	Online via broadcast to LogPass; Online via unicast to LogBase; Offline logging – finds LogBase and uploads (unicast)
Alarming	Activation via on/off button on device ('On Duty') optional via external link, e.g. case cover Signaling via green/red LED during 'On Duty'.
Power	Battery 3,6 V lithiumTCL (RMONI 2450mAh)
Battery life	>12 months at measuring rate 15min @ 25°C
Protection class	IP 54
Housing	PMMA glossy white
Dimensions	80x70x28mm
Weight	135g

All specifications in this document are subject to change without prior notice

Quality. In Control

Highlights	
Cost effective device	
Start/stop monitoring feature	
Clear in-alarm LEDs	
Compact design	
Easy to clean	
Internal or external sensor probe	
External switch "in use"	
Logging to the cloud	
Alarm via email and SMS	
Excellent replacement for loggers	



More information

BELGIUM

T +32 89 51 50 12 M info@rmoni.com

THE NETHERLANDS

T +31 74 265 77 87 M info@rmoni.com

IUQUI

Raise your quality standards with Rmoni